

Grilles, Registers and Diffusers • Accessories
Aluminum

Model: TRM • TITUS Rapid Mount Frame

Dimensions:
 Total width: $A + 1 \frac{1}{4}"$
 Ceiling Opening: $A + \frac{3}{8}"$
 Inside Opening: $A - 1"$

Ceiling Module	*Recommended Ceiling Opening	
	B	C
12 x 12	12 1/2	12 1/2
16 x 16	16 1/2	16 1/2
20 x 20	20 1/2	20 1/2
24 x 12	24 1/2	12 1/2
24 x 24	24 1/2	24 1/2
36 x 24	36 1/2	24 1/2
48 x 12	48 1/2	12 1/2
48 x 24	48 1/2	24 1/2
60 x 12	60 1/2	12 1/2

(Check actual dimensions before installation.)

A = Length of ceiling module

Dimensions are in inches

Frame Detail:
 Clip is adjustable up and down to fit varying ceiling thicknesses.
 Frame width: 1 1/8"
 Frame depth: 3/16"
 Ceiling thickness range: 1/2" to 7/8"

Standard Finish: #26 White.

General Description

- Model TRM TITUS Rapid Mount Frame allows T-bar, lay-in type diffusers (border Type 3) to be installed in surface mounting applications (border Type 1).
- TRM frame is installed in opening and secured in place using security clips. Screws are mounted flush in frame mounting holes.
- The TRM can be used to access ceiling plenum. Diffuser with flex connection can be lifted out of frame to access ceiling space.
- Rapid Mount Frame can be mounted in plaster or sheet rock ceiling.
- Material is aluminum with steel fasteners.