

**Louvered Supply Grilles and Registers • Steel**

Models:  ~~300RL • Double Deflection • Long Front Blades • 3/4" Blade Spacing~~  
 ~~300RS • Double Deflection • Short Front Blades • 3/4" Blade Spacing~~

~~Border Type 1 • Surface Mount~~

Screwdriver Slot Operator For Optional Damper

~~Optional Opposed Blade Damper~~

Note: When Damper Is Full Open, Add 3/8" To Overall Depth.

**Available Sizes (D" x D")**  
 Border Type 1 is available in sizes 6" x 4" through 48" x 48" in 2" increments in one piece construction. Odd and fractional sizes are available at additional cost. Sizes larger than 48" x 48" are shipped in multiple sections with joining strips for field assembly.

Note: Wall or duct opening should be duct size ± 1/8". All dimensions are in inches.

**Fastenings**

~~Type A • External Screw~~       ~~Type C • Concealed Screw~~

Available with Border Type 1 only. Single deflection blades shown for clarity. For actual blade configuration see above. Type C fastening not available with damper.

**Mounting Frames**

~~PF • Steel Plaster Frame~~       ~~PFA • Aluminum Plaster Frame~~

Surface Mounted Example      Recessed Mounted Example

Note: Wall opening should be listed duct size + 1/8" to listed duct size + 1/4". Plaster frame may be surface mounted or recess mounted.

**Accessories (Optional)**

Check  if provided

- Neck mounted opposed blade damper (galvanized steel)
- DS • Debris Screen (1/4" square mesh – galvanized steel)
- IS • Insect Screen (1/16" square mesh – galvanized steel)
- EQT • Earthquake tabs
- Other \_\_\_\_\_

**Standard Finish: #26 White**

Optional finish \_\_\_\_\_

**General Description**

- Available with front louvers vertical or horizontal.
- Front and rear louvers are individually adjustable.
- Insect and debris screens are not available when dampers are fitted.
- Material is steel.
- #8 x 1 1/4" lg. Phillip's flat head sheet metal screws (painted).
- All dimensions are ± 1/16".