

2000 Series - Line Voltage



Features

- White or Ivory
- Single pole and double pole
- Heat Only
- DP models include positive off
- Optional wire leads or terminals
- 22 Amps, 277 Volts AC

UPC#	MODEL	COLOR	DESCRIPTION
686334			
502849	S2022H10AA	White	Single Pole with leads, 22 Amp
502436	S2022H10AB	Ivory	
502856	D2022H10BA	White	Double pole with leads, 22 Amp
502443	D2022H10BB	Ivory	
502917	S2025H10AA	White	Single Pole with leads, 25 Amp
502924	D2025H10DA	White	Double pole with leads, 25 Amp

ET Series - Line Voltage



Features

- Single pole and double pole
- Heat only, cool only, & heat or cool
- DP models include positive off
- Celcius and Farenheight temperature scale
- Optional Thermometer
- 22 Amps, 277 Volts AC

UPC #	MODEL	DESCRIPTION
686334		
538725	AET5DWS	Double Pole 22 Amp, 120-277V with leads, Anticipator
538732	AET5SWS	Single Pole 22 Amp, 120-277V with leads, Anticipator
538886	ET5DS	Double Pole 22 Amp, 120-277V, Heat Only
538749	ET5D4S	Double Pole 22 Amp, 120-277V, 35-75°F Temp Range
538756	ET5DTS	Double Pole 22 Amp, 120-277V, with Thermometer, Heat Only
538763	ET5DWS	Double Pole 22 Amp, 120-277V, Heat Only with Leads
538770	ET5MS	Heat Only, 2 Stage
538787	ET5SS	Single Pole 22 Amp, 120-277V, Heat Only
538794	ET5S4S	Single Pole 22 Amp, 120-277V, 35-75°F Temp Range
538800	ET5SRS	Single Pole 22 Amp, Cooling Only
538817	ET5STS	Single Pole 22 Amp, Heat Only with Thermometer
538824	ET5SWS	Single Pole 22 Amp, Heat Only with Leads
538831	ETD5MS	Double Throw, 2 Stage Heat, 1 Stage Cool
538855	ETD5SS	Single Pole Double Throw Heat/Cool
538862	ETD5STS	Single Pole Double Throw Heat/Cool with Thermometer

EPET Series and HLT Series Hazardous Location



Features

- SPDT & DPDT Models
- Heat or cool compatible
- Celcius and Farenheight temperature scale
- Bi-Metal or capillary sensor
- Snap action switch
- Casting tapered top and bottom for 3/4" conduit
- 1/2" thick cast aluminum housing
- Dimension 5.75" x 6.375" x 5.57"

Motor Rating (full load): 3/4 HP @ 125V, 1 1/2 HP @250V  
 Pilot Duty Rating 125VA @ 24VAC  
 NEMA Class Seven Div. 1 Approved  
 Class I Group C & D, Class II Group E, F, & G  
 Not rated for Group B

UPC#	MODEL	DESCRIPTION	LOAD RATINGS	RANGE
686334				
538077	EPETD8D	DPDT - Bi-Metal	22A @120-277VAC	50-90°F
538107	EPETD8S	SPDT - Bi-Metal	22A @120-277VAC	50-90°F
528078	EPETP8D	DPDT - Bi-Metal	22A @120-480VAC	50-90°F
528061	EPETP8S	SPDT - Bi-Metal	22A @120-480VAC	50-90°F
523158	HLT-1	SPDT - Capillary	22A @120-277VAC	40-110°F
523165	HLT-2	DPDT - Capillary	22A @120-277VAC	40-110°F
Master ctn: 4 pcs, 24 lbs (varies slightly by model), 16" x 14.5" x 6"				
EPET Series incorporate plastic knob & Bi-Metal Sensor housing.				
HLT Series incorporates screwdriver temperature adjustment slot and all metal housing. External bulb and capillary sensor.				