

## GC 126 - 188

Model	RPM	CFM/ Watt at 0.1 SP	0.0 SP		.100 SP		.125 SP		.250 SP		.375 SP		.500 SP		.625 SP		.750 SP		.875 SP		1.000 SP		
			CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM
GC-126	550	2.5	70	0.3	53	0.3	48	0.3	32	0.7													
★ GC-128	750	2.8	94	0.8	82	0.9	79	0.9	63	1.0	49	1.3	37	2.0									
GC-146	900	2.9	114	1.2	105	1.2	103	1.2	90	1.3	77	1.5	64	2.0	50	2.5	36	3.0					
GC-148	1075	3.1	152	2.5	144	2.5	142	2.5	132	2.5	120	2.5	108	3.0	94	3.0	78	3.5	56	3.5			
GC-166	1100	3.1	164	3.0	157	3.0	155	3.0	145	3.0	133	3.0	119	3.0	105	3.0	88	3.5	66	3.5	40	3.5	
GC-168	1160	3.0	180	3.5	173	3.5	171	3.5	162	3.5	150	3.5	136	4.0	121	4.0	105	4.5	86	4.5	54	5.0	
GC-186	1100	2.4	231	5.5	226	5.5	225	5.5	218	5.5	209	5.5	199	5.0	186	5.0	170	5.0	151	5.0	129	4.5	
GC-188	1450	2.2	261	7.0	254	6.5	252	6.5	244	6.5	235	6.0	223	6.0	209	6.0	191	5.5	172	5.5	150	5.5	

★ ENERGY STAR® certified.

Performance certified is for Installation Type B: Free Inlet, Ducted Outlet. Performance ratings for GC-126 through GC-188 include the effects of inlet grille. Speed (RPM) shown is nominal. Performance is based on actual speed of the test. The sound ratings shown are loudness values in spherical sones at 5 ft. (1.5m) in a spherical free field calculated per AMCA Standard 301. Values shown are for Installation Type B: Free inlet spherical sone levels.

## GC 222 - 960

Model	RPM	CFM/ Watt at 0.1 SP	0.0 SP		.100 SP		.125 SP		.250 SP		.375 SP		.500 SP		.625 SP		.750 SP		.875 SP		1.000 SP		
			CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM
★ GC-222	1332	4.8	130	1.5	115	1.3	111	1.3	85	1.2													
★ GC-242	1483	5.2	158	2.5	142	2.0	137	2.0	112	1.5	56	1.3											
GC-322	1600	3.2	204	4.0	191	4.0	187	4.0	165	3.5	139	3.5											
GC-342	1725	3.0	268	5.0	252	5.0	248	4.5	224	4.5	195	4.5	153	4.5									
GC-422	1500	2.8	308	4.0	298	4.0	295	4.0	282	4.0	267	4.5	250	4.0	223	4.0							
GC-522	1400	2.7	213	1.5	208	2.0	207	2.0	201	2.0	194	2.5											
GC-542	1600	2.9	391	5.5	380	5.5	377	5.5	361	5.5	340	5.5	314	5.5	285	5.0	248	4.5					
GC-622	1400	3.3	501	3.5	486	3.5	482	3.5	461	3.0	433	3.0	392	3.0	339	3.0							
GC-642	1500	3.1	602	5.0	582	4.5	576	4.5	548	4.5	512	4.0	471	4.0	421	3.5	350	3.5					
GC-720	1375	2.4	709	5.5	687	5.5	682	5.5	653	5.5	619	5.0	578	5.0	535	5.0	480	4.5	385	4.5			
GC-740	1625	2.2	852	7.0	823	7.0	815	7.0	775	6.5	727	6.0	672	6.0	616	5.0	552	4.5	463	4.0	303	3.5	
GC-822	910	3.4	944	3.5	929	3.5	925	3.5	904	4.0	879	4.0	830	4.0									
GC-842	974	3.3	1187	5.0	1157	5.0	1149	5.0	1106	5.0	1043	4.5	905	4.5	637	3.5							
GC-862	1098	3.4	1433	7.0	1371	7.0	1355	6.5	1266	6.5	1149	5.5	995	5.0	775	4.0							
GC-920	925	3.6	1471	6.0	1427	6.0	1415	6.0	1356	6.0	1286	6.5	1190	6.5	1003	7.0							
GC-940	1040	3.5	1653	7.5	1582	7.5	1565	7.0	1481	7.0	1400	7.0	1293	7.0	1089	7.0							
GC-960	1112	3.4	1807	8.5	1716	8.0	1694	8.0	1588	7.5	1491	7.0	1386	7.0	1197	7.0							

★ ENERGY STAR® certified.

Performance certified is for Installation Type B: Free Inlet, Ducted Outlet. Performance ratings for GC-222 through GC-960 include the effects of inlet grille and backdraft damper. Speed (RPM) shown is nominal. Performance is based on actual speed of the test. The sound ratings shown are loudness values in spherical sones at 5 ft. (1.5m) in a spherical free field calculated per AMCA Standard 301. Values shown are for Installation Type B: Free inlet spherical sone levels.

## GC 1000 & 2000

Model	RPM	CFM/ Watt at 0.1 SP	0.0 SP		.100 SP		.125 SP		.250 SP		.375 SP		.500 SP		.625 SP		.750 SP		.875 SP		1.000 SP			
			CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones
GC-1000	1100	3.1	N/A	N/A	2230	7.8	2207	7.8	2090	7.6	1958	7.1	1796	6.7	1575	6.6	1090	6.6						
GC-2000	1140	2.8	N/A	N/A	3472	9.0	3441	9.0	3282	8.5	3105	8.5	2925	8.5	2736	8.0	2503	8.0	2147	8.0	1431	8.0		

Performance certified for GC-1000 and GC-2000 is for Installation Type B: Free inlet, ducted outlet. Performance ratings do not include the effects of appurtenances in the airstream. Speed (RPM) shown is nominal. Performance is based on actual speed of the test. The AMCA Certified Ratings Seal applies to air performance ratings only.